(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 28 July 2005 (28.07.2005)

PCT

(10) International Publication Number WO 2005/068696 A1

(51) International Patent Classification7:

D02G 03/02

(21) International Application Number:

PCT/US2003/041387

(22) International Filing Date:

22 December 2003 (22.12.2003)

(25) Filing Language:

English

(26) Publication Language:

English

- (71) Applicant (for all designated States except US): OTIS EL-EVATOR COMPANY [US/US]; Ten Farm Springs Road, Farmington, CT 06032 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): O'DONNELL, Hugh J. [US/US]; 289 Converse Street, Longmeadow, MA 01106 (US).
- (74) Agent: GASKEY, David J.; Carlson, Gaskey & Olds, 400 W. Maple Rd., Ste. 350, Birmingham, MI 48009 (US).

- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


of inventorship (Rule 4.17(iv)) for US only

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ELEVATOR TENSION MEMBER ASSEMBLY TECHNIQUES



(57) Abstract: An elevator belt (20) or rope (25) includes a plurality of tension members (22, 26, 46) encased within a polyurethane jacket (24, 28). Each tension member includes a plurality of strands (42), which are each made up of a plurality of wires (40). During the manufacturing process, broken wire (44, 54) ends are recaptured so that they do not protrude outward from the strands (42) or cords (46). A variety of recapture techniques are disclosed.

2005/068696 A1